

Office DECT 8000 **Quick Installation Guide**

This document provides summary instructions for a new installation of the Office DECT 8000 on a DCS or Compact II keyphone system. Refer to your *Office DECT 8000 Installation and Programming Manual* while reading these instructions.

1. Install the BSI card into the DCS or Compact II system as described in Chapter 4 of the manual. (*"Installation,"* pages 4-2 to 4-6.)

NOTE: The power to the DCS system must be switched OFF before attempting to install the BSI card.

2. Connect the BSI card to the DBS (DECT Base Station) as described in the manual. (Pages 4-6 to 4-10.)

When the DBS is connected correctly, the left and centre LEDs on the DBS will light. Please note that the DBS is not yet operational.

3. Enter programming mode and enter an *Authentication Code* and *System ID* in MMC 737. (Page 5-3.)
 - The system will now download the BSI software to the DBS. The LEDs on the front of the DBS will flash in various sequences. The BSI software download can take up to 5 minutes for each DBS connected, so be patient.
 - Once the DBS has initialised, the left-hand LED will light steady, the centre LED will go off and the right-hand LED will flash.

(See the table of LEDs on page 6-8.)

4. Enter programming mode again and enable registration in MMC 744. (Page 5-10.)
5. Register your Office DECT 8000 handsets as described in Chapter 4 of the manual (page 4-18) or as shown in the user guide supplied with each handset (page 11).
6. Once all handsets have been registered, disable DECT registration in MMC 744 **immediately** to prevent unauthorised use.

7. Test DECT handsets for functionality.